


WAAS CH 40223 W26A	APP CRS 265°	Rwy Idg TDZE Apt Elev	9025 3962 3962
--	------------------------	-----------------------------	---


RNAV (GPS) Y RWY 26L

EL PASO INTL (ELP)

RNP APCH-GPS.		MALSR	MISSED APPROACH: Climb to 4380 then climbing right turn to 7500 direct FABAN and hold.	
Circling NA for Cat D west of Rwy 4-22. For inop ALS, increase LP and LNAV Cat A/B visibility to 1 SM, and Cat C/D to 1½ SM.				
D-ATIS 120.0 254.3	EL PASO APP CON 124.25 298.85	EL PASO TOWER 118.3 239.275	GND CON 121.9 348.6	CLNC DEL 125.0 379.1



ELEV 3962	D	TDZE 3962
-----------	----------	-----------



4380	7500	FABAN	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 75).				
CATEGORY		A		B		C	D
LP	MDA	4380-¾					418 (500-¾)
LNAV	MDA	4380-¾					418 (500-¾)
	CIRCLING	4420-1 458 (500-1)		4440-1 478 (500-1)		4480-1½ 518 (600-1½)	4680-2¼ 718 (800-2¼)