

LOC I-HLN	APP CRS	Rwy Idg	9000
110.1	271°	TDZE	3852
		Apt Elev	3877

ILS Y or LOC Y RWY 27
HELENA RGNL (HLN)

ADF or RADAR required for procedure entry. ADF or DME required.

⚠

⚠

❄ -17°C

Circling NA to Rwy 10 and 28. Circling Rwy 5, 23, 35 NA at night. Inop table does not apply to S-LOC 27 all Cats. For inop ALS, increase S-ILS 27 all Cats visibility to 1½ SM, ORYON fix minimums: S-LOC 27 Cat C/D/E visibility to 2 SM. Holding at HAU NDB authorized for Cat A and B aircraft only. Circling NA for Cats D and E south of Rwy 9-27.
*DME from HLN VORTAC. DME use requires simultaneous reception of I-HLN and HLN DME.

MALSR

MISSED APPROACH: Climb to 4700 then climbing right turn to 9300 on heading 021° and on HLN VORTAC R-340 to WOKEN INT and hold, continue climb-in-hold to 9300.

ATIS 120.4	HELENA APP CON* 119.5 229.4	HELENA TOWER* 118.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
---------------	--------------------------------	---------------------------------------	------------------	------------------

4700 9300 HLN WOKEN		ELEV 3877 D TDZE 3852			
↑ hdg 021° R-340					
HLN 1.9 ORYON HLN 5.2		One Minute Holding Pattern			
5640 7100 7400 14000 7400		GS 3.00° TCH 55			
2.2 NM 3.3 NM 3.3 NM 2.3 NM					
CATEGORY	A	B	C	D	E
S-ILS 27	4496-1½ 644 (700-1½)				
S-LOC 27	5640-1¼ 1788 (1800-1¼)	5640-1½ 1788 (1800-1½)	5640-3	1788 (1800-3)	
CIRCLING	5640-1¼ 1763 (1800-1¼)	5640-1½ 1763 (1800-1½)	6000-3	2123 (2200-3)	
ORYON FIX MINIMUMS*					
S-LOC 27	4600-½ 748 (800-½)	4600-¾ 748 (800-¾)	4600-1¾	748 (800-1¾)	
CIRCLING	4640-1 763 (800-1)	4600-1¼ 923 (1000-1¼)	6000-3	2123 (2200-3)	
REIL Rwys 9, 17 and 35 MIRL Rwys 5-23 and 17-35 HIRL Rwy 9-27					
FAF to MAP 8.7 NM					
Knots 60 90 120 150 180 Min:Sec 8:42 5:48 4:21 3:29 2:54					

HELENA, MONTANA
Amdt 4 23FEB23

46°36'N-111°59'W

HELENA RGNL (HLN)
ILS Y or LOC Y RWY 27

NW-1, 22 FEB 2024 to 21 MAR 2024

NW-1, 22 FEB 2024 to 21 MAR 2024