

LOC I-ABE <u>110.7</u>	APP CRS 063°	Rwy Idg TDZE Apt Elev	7599 394 394
----------------------------------	------------------------	-----------------------------	---

ILS RWY 6 (SA CAT I & II)
LEHIGH VALLEY INTL (ABE)

T SA CAT I: Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH. SA CAT II: Reduced lighting: Requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown.

MALSR



MISSED APPROACH: Climb to 3000 on heading 063° and STW R-243 to MUDRE INT/STW 20.5 DME/RADAR and hold.

ATIS 126.975	ALLETOWN APP CON 119.65 124.45 351.8	ALLETOWN TOWER 120.5 257.95	GND CON 121.9 257.95	CLNC DEL 124.05 257.95
-----------------	---	--------------------------------	-------------------------	---------------------------

LOC I-BXY 111.9	APP CRS 135°	Rwy ldg TDZE Apt Elev
		5800 386 394

ILS or LOC RWY 13

LEHIGH VALLEY INTL (ABE)



⚠

For inoperative MALSR, increase IZKIP fix minimums S-LOC 13 Cat C/D visibility to 1 mile.


MALSR

MISSED APPROACH: Climb to 3000 then climbing left turn to 3000 on heading 060° and on SBJ VOR/DME R-295 to IZZI INT and hold.

ATIS 126.975	ALLENTOWN APP CON 119.65 124.45 351.8	ALLENTOWN TOWER 120.5 257.95	GND CON 121.9 257.95	CLNC DEL 124.05 257.95
------------------------	---	--	--------------------------------	----------------------------------



CATEGORY	A	B	C	D
S-ILS 13	586-1/2 200 (200-1/2)			
S-LOC 13	1260-1/2 874 (900-1/2)	1260-3/4 874 (900-3/4)	1260-2 874 (900-2)	
CIRCLING	1260-1 1/4 866 (900-1 1/4)	1260-2 1/2 866 (900-2 1/2)	1600-3 1206 (1300-3)	
IZKIP FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 13	740-1/2 354 (400-1/2)	740-5/8 354 (400-5/8)		
CIRCLING	840-1 446 (500-1)	900-1 506 (600-1)	1180-2 1/4 786 (800-2 1/4)	1600-3 1206 (1300-3)



LOC I-ABE 110.7	APP CRS 063°	Rwy Idg TDZE Apt Elev 7599 394 394
---------------------------	------------------------	--


ILS or LOC RWY 6
LEHIGH VALLEY INTL (ABE)

▽
▲ * RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 on heading 063° and STW R-243 to MUDRE INT/STW 20.5 DME/RADAR and hold.

ATIS 126.975	ALLENTOWN APP CON 119.65 124.45 351.8	ALLENTOWN TOWER 120.5 257.95	GND CON 121.9 257.95	CLNC DEL 124.05 257.95
------------------------	---	--	--------------------------------	----------------------------------



VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 74).

One Minute Holding Pattern

JISTO INT RADAR

SHAGY INT RADAR

GS 3.00° TCH 57

4800 3000

243° 063°

2400

6.7 NM 6.1 NM

CATEGORY	A	B	C	D
S-ILS 6*	594/24 200 (200-½)			
S-LOC 6	920/24 526 (600-½)		920/55 526 (600-1)	
C CIRCLING	920-1 526 (600-1)		1180-2¼ 786 (800-2¼) 1600-3 1206 (1300-3)	

ELEV 394 **D** TDZE 394

REIL Rwy 24 and 31
HIRL Rwy 6-24 and 13-31


FAF to MAP 6.1 NM

Knots	60	90	120	150	180
Min:Sec	6:06	4:04	3:03	2:26	2:02

NE-4, 22 FEB 2024 to 21 MAR 2024

NE-4, 22 FEB 2024 to 21 MAR 2024

ILS or LOC/DME RWY 24
LEHIGH VALLEY INTL (ABE)




ATIS
126,975

ALLENTOWN APP CON
119.65 124.45 351.8



ALLENTOWN TOWER
120.5 257.95

GND CON
121.9 257.95

CLNC DEL
124,05 257,95

ELEV 394TD

3



VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 71).

One Minute Holding Pattern



CATEGORY	A	B	C	D
S-ILS 24	587/40 200 (200-¾)			
S-LOC 24	800/55 413 (500-1)	800/60 413 (500-1¼)		
C CIRCLING	900-1 506 (600-1)	1180-2¼ 786 (800-2¼)	1600-3 1206 (1300-3)	

RNAV (GPS) RWY 13

LEHIGH VALLEY INTL (ABE)

MISSED APPROACH: Climb to 3000 direct KOCEC and on track 084° to LZZI and hold.

CLNC DEL
124.05 257.95





WAAS CH 40332 W24A	APP CRS 243°	Rwy Idg TDZE 387 Apt Elev 394	7089 387 394
--	------------------------	---	---

RNAV (GPS) RWY 24

LEHIGH VALLEY INTL (ABE)

RNP APCH. ▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F).		MISSED APPROACH: Climb to 3000 direct SURGE and on track 266° to ETX VOR/DME and hold.		
ATIS 126.975	ALLENTOWN APP CON 119.65 124.45 351.8	ALLENTOWN TOWER 120.5 257.95	GND CON 121.9 257.95	CLNC DEL 124.05 257.95




WAAS CH 69432 W06A	APP CRS 063°	Rwy Idg 7599 TDZE 394 Apt Elev 394
--	------------------------	---

RNAV (GPS) RWY 6

LEHIGH VALLEY INTL (ABE)

RNP APCH.	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). For inop ALS, increase LNAV Cat C/D visibility to 1½ SM. **RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 3000 direct FONUP and hold.
-----------	---	-----------	---

ATIS 126.975	ALLENTOWN APP CON 119.65 124.45 351.8	ALLENTOWN TOWER 120.5 257.95	GND CON 121.9 257.95	CLNC DEL 124.05 257.95
------------------------	---	--	--------------------------------	----------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).					3000	FONUP
GP 3.00° TCH 56					*LNAV only.	
JISTO					SHAGY	
3000					2400	
063°					*1400	
2400					*1.3 NM to RW06	
6.7 NM					RW06	
3.1 NM					1.7 NM	
1.3 NM					1.3 NM	
CATEGORY	A		B		C	
LPV DA **	594/24		200 (200-½)			
LNAV/ DA VNAV	644/24		250 (300-½)			
LNAV MDA	840/24 446 (500-½)		840/45 446 (500-¾)			
CIRCLING	900-1 506 (600-1)		1180-2¼ 786 (800-2¼)		1600-3 1206 (1300-3)	

REIL Rwy 24 and 31
HIRL Rwy 6-24 and 13-31

▼ ▲ NA		MISSED APPROACH: Climbing right turn to 3100 direct FJC VORTAC then via FJC R-008 to BLOWN/6 DME and hold.		
ATIS	ALLENTOWN APP CON	ALLENTOWN TOWER	GND CON	CLNC DEL
126.975	119.65 124.45 351.8	120.5 257.95	121.9 257.95	124.05 257.95

