



WAAS CH 69620 W14A	APP CRS 139°	Rwy Idg TDZE Apt Elev	4401 1319 1324
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 14
BEATRICE MUNI (BIE)

RNP APCH - GPS.		MISSED APPROACH: Climb to 3600 direct SHIRS and hold.
AWOS-3 125.325	MINNEAPOLIS CENTER 126.4 317.7	UNICOM 122.8 (CTAF) 0



ELEV 1324	D	TDZE 1319
-----------	----------	-----------



4 NM Holding Pattern				MIDIE	TADGE	WUBIL 1.9 NM to RW14	SHIRS
6000 ← 319°				3600	3000	1960	3600
GP 3.00°				139°	139°	1.2 NM to RW14	↑
TCH 45				7.4 NM	3.2 NM	0.7	4 NM
CATEGORY	A	B	C	D			
LPV DA	1569-1			250 (300-1)			
LNAV/VNAV DA	1569-1			250 (300-1)			
LNAV MDA	1760-1		441 (500-1)	1760-1 3/8		441 (500-1 3/8)	
C CIRCLING	1760-1 436 (500-1)	1800-1 476 (500-1)	2000-2 676 (700-2)	2100-2 1/2 776 (800-2 1/2)			


WAAS CH 58320 W32A	APP CRS 319°	Rwy Idg TDZE Apt Elev	4401 1312 1324
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32


BEATRICE MUNI (BIE)

RNP APCH - GPS.	MISSED APPROACH: Climb to 3600 direct MIDIE and hold.
Rwy 32 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.	

AWOS-3 125.325	MINNEAPOLIS CENTER 126.4 317.7	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



ELEV 1324	D	TDZE 1312
-----------	----------	-----------





WAAS CH 61099 W36A	APP CRS 356°	Rwy Idg TDZE 1307 Apt Elev 1324
--	------------------------	---

RNAV (GPS) RWY 36

BEATRICE MUNI (BIE)


RNP APCH - GPS.	MALSR	MISSED APPROACH: Climb to 3900 direct HAMUL and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When ALS inop increase LNAV Cats A/B to 1 SM. Inop table does not apply to LPV and LNAV/VNAV all Cats.		

AWOS-3 125.325	MINNEAPOLIS CENTER 126.4 317.7	UNICOM 122.8 (CTAF)
--------------------------	--	---



ELEV 1324	D	TDZE 1307
-----------	---	-----------

REIL Rwy's 14 and 32
MIRL Rwy's 14-32 and 18-36





CATEGORY	A	B	C	D
LPV DA	1507-¾ 200 (200-¾)			
LNAV/VNAV DA	1557-¾ 250 (300-¾)			
LNAV MDA	1840-¾ 533 (600-¾)	1840-1 533 (600-1)		
CIRCLING	1840-1 516 (600-1)	2000-2 676 (700-2)	2100-2½ 776 (800-2½)	

VOR BIE 110.6	APP CRS 176°	Rwy Idg TDZE Apt Elev 5602 1324 1324
-------------------------	------------------------	--

VOR RWY 18

BEATRICE MUNI (BIE)




DME required for procedure entry.		MISSED APPROACH: Climb to 3000 then climbing right turn to 3300 direct BIE VOR and hold.
	Rwy 18 helicopter visibility reduction below ¾ SM NA.	
AWOS-3 125.325	MINNEAPOLIS CENTER 126.4 317.7	UNICOM 122.8 (CTAF)



VOR BIE 110.6	APP CRS 350°	Rwy Idg 5602 TDZE 1307 Apt Elev 1324	VOR RWY 36 BEATRICE MUNI (BIE')
-------------------------	------------------------	---	------------------------------------

DME required for procedure entry.	MALSR	MISSED APPROACH: Climb to 3000 then right turn direct BIE VOR and hold.
For inop ALS, increase S-36 Cats A/B visibility to 1 SM and Cats C/D visibility to 2 SM.		

AWOS-3 125.325	MINNEAPOLIS CENTER 126.4 317.7	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



NC-2, 22 FEB 2024 to 21 MAR 2024

NC-2, 22 FEB 2024 to 21 MAR 2024