

WAAS CH 93732 W32A	APP CRS 322°	Rwy Idg TDZE 1130 Apt Elev 1136
--	------------------------	---

RNAV (GPS) RWY 32


MORRIS MUNI/CHARLIE SCHMIDT FLD (MOX)

RNP APCH-GPS.

Circling NA to Rwy 4 and 22. Baro-VNAV and VDP NA when using Benson altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Benson altimeter setting and increase LPV DA to 1388 feet and LNAV/VNAV DA to 1477 feet. Increase all MDAs 60 feet and visibility LNAV Cat C ½ SM and visibility Circling Cat C ¼ SM.

MISSED APPROACH: Climb to 3000 direct ZITOG and hold.

AWOS-3PT 118.6	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



3000	ZITOG	SISOE	3 NM to RW32	WIVKA	3000	EXJUP	4 NM Holding Pattern	6000	3500	GP 3.00°	TCH 40
1 NM	1 NM	2 NM	2.8 NM	7.8 NM							
CATEGORY	A	B	C	D							
LPV DA	1330-1	200 (200-1)			NA						
LNAV/VNAV DA	1419-1	289 (300-1)			NA						
LNAV MDA	1480-1	350 (400-1)			NA						
CIRCLING	1560-1 424 (500-1)	1600-1 464 (500-1)	1860-2 724 (800-2)		NA						