

LOM SH
375

APP CRS
047°

Rwy Idg
TDZE
Apt Elev
6002
1184
1201

AL-5369 (FAA)

NDB RWY 5

SHENANDOAH VALLEY RGNL (SHD)

When local altimeter setting not received, use Charlottesville altimeter setting and increase all MDAs 140 feet and visibility S-5 and Circling Cat C ½ SM, Cat D ¼ SM.

MALSR

MISSED APPROACH: Climb to 2400 then climbing left turn to 3600 direct SH LOM and hold.

AWOS-3 124.925	POTOMAC APP CON 132.85 323.125	CLNC DEL 118.35	UNICOM 123.0 (CTAF) 0
--------------------------	--	---------------------------	---------------------------------

CATEGORY	A	B	C	D
S-5	1760-¾ 576 (600-¾)	1760-1 576 (600-1)	1760-1½ 576 (600-1½)	
CIRCLING	1760-1 559 (600-1)	1900-2 699 (700-2)	2060-2¾ 859 (900-2¾)	

ELEV 1201 D TDZE 1184

REIL Rwy 23 0

HIRL Rwy 5-23 0

1246

6002 X 150

0.4% UP

047°

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

STAUNTON-WAYNESBORO-HARRISONBURG, VIRGINIA

SHENANDOAH VALLEY RGNL (SHD)

Amdt 10A 22APR21

38°16'N-78°54'W

NDB RWY 5